

COMMERCIAL POOL

Natural Pool Water Treatment

PZ2-16 Commercial Pools

The PZ2-16 for pools up to 400,000 gal (1.5 million liters) is a compressor driven ozone system which can inject ozone under almost any hydraulic condition including pools with in-floor cleaners. The system is built with commercial grade compressors, solid state power supplies, our advanced hybrid ozone generator and muffling to ensure quiet operation.



Upgrade Optional Skid Mount Includes:

- Full Turnkey Water In
Water Out Installation
- Water Circulation Pump
- Counter Flow Contacting
- Static Mixer
- Contacting/degas Column

Additional Upgrade Options:

- ORP/pH Monitoring
- Ozone Destruct
- Ozone Monitoring
- Below Water Solenoid Kit



T-O₃ NATURAL TECHNOLOGY

Reduces Chemical Usage, Improves Sanitation, Eliminates Odors, Produces Crystal Clear Water

No recurring maintenance or special skills are required. All PZ2 residential and commercial systems carry a two-year warranty; the compressor carries a one-year warranty. Contact a Prozone engineer for further engineering details on the PZ2 Series.

Electrical System Options

- 110/220 VAC, 60 hz
- 220/240 VAC, 60 hz
- 230 VAC, 50 hz
- Universal Solid State Inverter Ballast: 90 VAC to 270 VAC

Front of PZ2-16 on Optional Skid Mount Upgrade



NSF Rated Installation Kit Available

- Kit includes NEMA housing, contacting system, and degassing column; boost pump optional

Specifications

- Arc Life (Nominal): 20,000 Hours
- Compressor Life: (Nominal): 40,000 Hours
- Operating Temperature: -25° F. to +140° F.
- Storage Temperature: -60° F. to +160° F.



Back of PZ2-16 on Optional Skid Mount Upgrade



Ozone Output	5 grams/hr
Commercial Pool Sizing	Chlorine 400,000 gal Bromine 300,000 gal
Dimensions of PZ2-16	24" X 7" X 50"
Weight without skid	107 lbs
Dimensions of PZ2-16 with Skid Mounts	42" X 37" X 60"